

Z-FLEX™ - 26 oz Black Vermiculite Coated Fiberglass Welding Blanket



For heavy duty welding applications - sparks, spatter, and slag.

- 26 oz black vermiculite coated fiberglass
- Protects against sparks, spatter, and slag
- Temperature rating: 1200°F
- Weight: 26 oz/yd²
- Thickness: .050"
- Grommeted on all four sides, 24" apart
- FM approved
- Not recommended for stress relief
- Available with no grommets
- Available in multiple standard sizes, custom, and rolls



Our technical sales representatives will assist you with your project requirements.
Give us a call today at **847-439-4565** for a quote!



Specifications

ATTRIBUTE	VALUE
PRODUCT CATEGORY	Welding Blankets and Roll Goods
PRODUCT TYPE	Vermiculite coated fiberglass
MATERIAL	Fiberglass
TEMPERATURE RATING	1200°F
THICKNESS	.050"
COATING	Vermiculite coating
GROMMETS	3/8" brass grommets, 24" apart on all four sides
FOR STRESS RELIEF	No
ABRASION RESISTANCE	Good
COMPLIANCE 1	FM approved
COLOR	Black
SIZE	Available in multiple standard sizes, custom, and rolls
SPECIAL FEATURE 1	Not recommended for stress relief

Our technical sales representatives will assist you with your project requirements.
Give us a call today at **847-439-4565** for a quote!



Part numbers for ordering

BLANKET		ROLLS	
S Size	Part number	Size	Part number
6' x 6'	397-6X6	40" W x 50 YD	397-40
6' x 8'	397-6X8	60" W x 50 YD	397-60
8' x 8'	397-8X8	72" W x 50 YD	397-72
8' x 10'	397-8X10		
10' x 10'	397-10X10		
Custom	397-C		

Our technical sales representatives will assist you with your project requirements.
Give us a call today at **847-439-4565** for a quote!

