Page 1 of 3

Red Silicone - 32 oz Silicone Coated Fiberglass Welding Blanket



For medium duty welding applications - sparks, spatter, and light slag. Good abrasion resistance.

- 32 oz red silicone coated fiberglass
- Protects against sparks, spatter, and light slag
- Temperature rating: 1000°F
- Weight: 32 oz/yd²
- Thickness: .035"
- Grommeted on all four sides, 24" apart
- Good abrasion and oil resistance
- Not recommended for stress relief
- FM approved
- Available with no grommets
- Available in multiple standard sizes, custom, and rolls













Page 2 of 3

Specifications

ATTRIBUTE	VALUE		
PRODUCT CATEGORY	Welding Blankets and Roll Goods		
PRODUCT TYPE	Silicone coated fiberglass		
MATERIAL	Fiberglass		
TEMPERATURE RATING	1000°F		
THICKNESS	.035"		
COATING	Silicone coating		
GROMMETS	3/8" brass grommets, 24" apart on all four sides		
FOR STRESS RELIEF	No		
ABRASION RESISTANCE	Good		
COMPLIANCE 1	FM approved		
COLOR	Red		
SIZE	Available in multiple standard sizes, custom, and rolls		
SPECIAL FEATURE 1	Good abrasion and oil resistance		
SPECIAL FEATURE 2	Not recommended for stress relief		





Page 3 of 3

Part numbers for ordering

BLANKET		ROLLS	
S Size	Part number	Size	Part number
6' x 6'	379-6X6	60" W x 50 YD	379-60
6' x 8'	379-6X8		•
Custom	379-C		

