

age 1 of 3

BlackFlex™ - 28 oz Black Heavy Acrylic Coated Fiberglass Welding Blanket



For medium duty welding applications - sparks and spatter. Good abrasion resistance.

- 28 oz black heavy coated fiberglass
- Protects against sparks and spatter
- Temperature rating: 1000°F
- Weight: 28 oz/yd²
- Thickness: .050"
- Grommeted on all four sides, 24" apart
- Excellent abrasion resistance
- Not recommended for stress relief
- FM approved
- Available with no grommets
- Available in multiple standard sizes, custom, and rolls













Page 2 of 3

Specifications

ATTRIBUTE	VALUE	
PRODUCT CATEGORY	Welding Blankets and Roll Goods	
PRODUCT TYPE	Acrylic coated fiberglass	
MATERIAL	Fiberglass	
TEMPERATURE RATING	1000°F	
THICKNESS	.050"	
COATING	Acrylic coating	
GROMMETS	3/8" brass grommets, 24" apart on all four sides	
FOR STRESS RELIEF	No	
ABRASION RESISTANCE	Excellent	
COMPLIANCE 1	FM approved	
COLOR	Black	
SIZE	Available in multiple standard sizes, custom, and rolls	
SPECIAL FEATURE 1	Excellent abrasion resistance	
SPECIAL FEATURE 2	Not recommended for stress relief	





Page 3 of 3

Part numbers for ordering

BLANKET	
S Size	Part number
3' x 4'	376-3X4
6' x 6'	376-6X6
6' x 8'	376-6X8
6' x 10'	376-6X10
8' x 8'	376-8X8
8' x 10'	376-8X10
10' x 10'	376-10X10
Custom	376-C

ROLLS	
Size	Part number
40" W x 50 YD	376-40
60" W x 50 YD	376-60
72" W x 50 YD	376-72